



CUSHMAN

MODEL: HAULSTER
TYPE: HIGH SPEED GASOLINE POWERED
MANUAL TRANSMISSION TRUCK
MODEL YEAR: 2012

Part No.: 84060



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

- Engine:** 32.2 hp (24.0 kW) rated, 4 cycle, 40.3 cid (660 cc) EFI, three cylinder, liquid-cooled by Suzuki
- **Valve Train:** 12 overhead valves, dual overhead cam, chain drive
 - **Lubrication:** Pressurized oil system, spin-on filter 3.3 qt (3 L) capacity
 - **Air Cleaner:** Dry cartridge with evacuator valve
 - **Fuel System:** Electronic fuel injection
 - **Ignition:** Solid-state
- Electrical:** Starter, 60 amp alternator, 12 Volt maintenance free battery (580 cca, 85 minute reserve)
- Ignition:** Electronic with cam trigger, electronic advance & RPM limiter
- Drive Train:** 5 Speed manual transmission. Low creeper first gear. All forward gears synchronized
- Clutch:** 6.7 in (17 cm) dry single disc & pressure plate
- Brakes:** 4-wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo] Dual master cylinder with remote reservoir, Mechanical hand brake
- Rear Axle:** Differential with hypoid gears
- Capacity:** Seating for 2 persons

PRODUCT OVERVIEW

Dimensions

Overall Length	136.0 in (345 cm)
Overall Width	53.0 in (135 cm)
Overall Height (to top of ROPS)	74.0 in (188 cm)
Wheel Base	88.2 in (224 cm)
Front Wheel Track	42.0 in (107 cm)
Rear Wheel Track	44.0 in (112 cm)
Gnd Clearance @ Differential	5.0 in (13 cm)
Cargo Deck Size	47.4 in (120 cm) W x 72 in (183 cm) L
Cargo Deck Material	Diamond pattern steel

Vehicle Power

Power Source	4 cycle, 40.3 ci (660 cc) EFI, 3 cylinder
Valve Train	12 valve, dual OHV/OHC. Chain drive
Horsepower (kW)	32.2 hp (24.0 kW) @ 4450 rpm (governed)
Electrical System	12 Volt starter. 60 amp alternator
Battery (Qty, Type)	One 12 Volt maintenance free
Key or Pedal Start	Key start
Air Cleaner	Dry cartridge
Lubrication	Pressurized oil system
Oil Filter	Spin-on
Cooling System	Liquid cooled
Fuel Capacity	7.0 gallon (26.5 L) tank
Transmission	Synchronized 5 Speed manual
Gear Selection	5 speeds forward - Neutral - Reverse
Gear Shift location	Dash
Rear Axle Ratio	11.16:1

Performance

Seating Capacity	2 Persons
Curb Weight	1540 lb (699 kg)
Vehicle load capacity	2400 lb (1090 kg)
Outside Clearance Circle	20.2 ft (6.2 m)
Intersecting Aisle Clearance	N/A
Speed (Governed, Level Gnd)	25.5 mph ± 0.5 mph (41 kph ± 0.8 kph)
Towing Capacity	2400 lb (1090 kg)

Steering & Suspension

Steering	Automotive power
Front Suspension	Double A-arm independent w/spring over shocks
Rear Suspension	Multiple leaf springs
Rear Axle	Differential with hypoid gears
Service Brake	4 Wheel 7.9 (20 cm) hydraulic drum
Parking Brake	Mechanical hand brake
Front Tires	USA Trail 20.5 x 8 - 10 (Load range C)
Rear Tires	USA Trail 20.5 x 8 - 10 (Load range C)

Body & Chassis

Frame	Unitized welded steel channel. E-coat finish
Front Body & Finish	Polyethelene
Rear Body & Finish	Steel with rubber fender flairs
Storage	Hinged front cowl
Standard Color	Yellow
Roll Over Protective Structure	2 post ROPS - standard

Some items shown may be optional equipment

